



**WILSONART**<sup>®</sup>  
INTERNATIONAL

### General Description

An emulsion of water, starch and polyvinyl acetate suitable for bonding decorative laminate to wood products. This product does not require stirring before use.

### Applications

- Glue spreader/cold press laminating
- Consumer or professional use
- Formulated for bonding paper-backed products

### Applications to Avoid

- Tempered hardboard products
- Fire retardant treated board products
- Boards treated to be moisture resistant
- Low pressure melamine surfaces
- Metallic, polyester and painted surfaces
- Wheatboard and strawboard

### Availability

- 2,500-pound totes (returnable)
- 500-pound drums

### Storage/Shelf Life

- DO NOT ALLOW PRODUCT TO FREEZE.
- Close container tightly when not in use. Store off floor in a well ventilated area.
- Rotate stock.
- Shelf life expires 1 year from manufacture date.

### General Use Instructions

- Ensure substrates and adhesive are above 65° F.
- Best results are achieved between 70° F and 85° F.
- Surfaces must be clean and dry.

### Cold Press Laminating Instructions

- Follow the glue spreader manufacturer's recommendations.
- Use a dual durometer roller (Black Bros. #A2158, 16 x 1/2" pattern)
- Select a groove pattern appropriate for PVA glue.
- Apply 6-8 wet mils with glue spreader.
- Open time is approximately 5 minutes.
- Closed time is approximately 20 minutes.
- Press time is 30-60 minutes at 40-50 psi.
- Wait at least 2-3 hours after pressing to machine.
- Wait 24 hours after pressing for heavy machining.

### Physical Properties

<b>Color:</b>	White
<b>Viscosity:</b>	5750 cps (typical)
<b>Density:</b>	9.1 lbs/gallon
<b>Solids Content:</b>	43.0% ± 2.0%
<b>pH:</b>	4-6 (typical)
<b>VOC Content:</b>	<20 g/L (Meth. 24)
<b>VHAP Content:</b>	<0.043 lbs/lbs solids
<b>Coverage (Spreader):</b>	~229 ft <sup>2</sup> /gal @ 7 wet mils

**\*GREENGUARD<sup>®</sup> Certified**

**\*Complies with SCAQMD, Rule 1168**

**\*Qualifies for LEED<sup>®</sup>-NC & CI EQ Credit 4.1:**

*Low Emitting Materials: Adhesives & Sealants*

**\*Qualifies for LEED<sup>®</sup>-NC & CI EQ Credit 4.4:**

*Laminating adhesives shall contain no added urea-formaldehyde resins.*

### Clean-up/Disposal

- Clean with hot tap water while adhesive is wet.
- Removal of dried adhesive is very difficult.
- Use diluted ammonia to clean dry adhesive.
- Washwater is RCRA non-hazardous.
- Dispose of waste in accordance with regulations.

### Primary Contents

- Vinyl acetate homopolymer (CAS 9003207)
- Water (CAS 7732185)
- NJTSRN #990001
- Starch (CAS 9005258)
- Polyvinyl Alcohol (CAS 9002895)



**PVA ADHESIVE**  
**FOR COLD PRESS APPLICATIONS**



## PVA ADHESIVE FOR COLD PRESS APPLICATIONS

### **GREENGUARD® Indoor Air Quality Standard for Low Emitting Products**

GREENGUARD Indoor Air Quality Certified Products meet the following minimum emission requirements:

**Category:** Adhesives/Sealants

<u>Emission Types</u>	<u>Measure</u>
Individual VOCs	<0.1 TLV
Formaldehyde	<0.05 ppm (<0.06 mg/m <sup>3</sup> )
4-phenylcyclohexane	<0.0065 mg/m <sup>3</sup>
Styrene	<0.07 mg/m <sup>3</sup>
Total VOCs	<0.05 mg/m <sup>3</sup>
Total aldehydes	<0.1 ppm

### **Proposition 65 Warning**

This product contains substances known to the State of California to cause cancer or reproductive harm.

### **Volatile Organic Compounds (VOC):**

The use, supply, sale or offer for sale of this product in certain states and localities may be prohibited if it exceeds certain VOC limits. Please check state and local regulations for any prohibitions on the sale and use of this product.

### **Safety**

- Non-Flammable
- Mildly irritating to eyes.
- May irritate sensitive skin.
- Inhalation may irritate respiratory tract.
- See MSDS for complete data
- 24 hr. Chemtrec emergency number:  
1-800-424-9300 (US); 703-527-3887 (International)

### **Warranty**

Wilsonart International, Inc. warrants to the user that this product is free of defects for a period of one (1) year from the date of manufacture when it is applied in accordance with manufacturer's instructions or the manufacturer will replace the container at no cost or additional charge to the user, provided the unused portion of the product is returned to the place of purchase within 15 days of the date of purchase. This warranty does not apply to (I) products that are purchased after the expiration of the manufacturer's recommended shelf life as stated on this technical data sheet, (II) misuse or mishandling of the product, (III) improper storage, or (IV) improper fabrication using this product. NO OTHER WARRANTIES, EXPRESS OR IMPLIED ARE MADE, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. UNDER NO CIRCUMSTANCES SHALL THE MANUFACTURER BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE, OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO FABRICATOR, INSTALLER, DEALER, AGENT OR EMPLOYEE OF WILSONART INTERNATIONAL, INC. HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATION OF THIS WARRANTY. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state. Therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of product.

### **For More Information**

- [www.wilsonartadhesives.com](http://www.wilsonartadhesives.com) for:
  - Tech Data Sheets
  - Material Safety Data Sheets (MSDS)
  - Adhesive Quick Reference Chart
  - Certified Product Data Sheets (CPDS)
- Customer Service Line 1-800-433-3222
- Wilsonart Adhesives Division  
10601 NW HK Dodgen Loop  
Temple, TX 76503-6110



©2011 Wilsonart International, Inc.  
Rev. 01/2011